

CONCRETE

NATURAL STONE
AGGLOMERATES
TUMBLED MARBLE
GRANITE
PEBBLES AND
COBBLESTONES



Half of this porous stone has been treated with Fila products while the other half has not. On the treated side (right), the drip-effect of water is visible. On the untreated side the water has penetrated the floor.

WHAT IT'S FOR

- Protects exterior pavings from water and humidity
- Makes walls and claddings water-repellent
- Ideal for brick veneers and concrete
- Protects grout joints
- Protects from wear caused by atmospheric agents

ADVANTAGES

- Gives a long-lasting, renewable protection that allows the material to breathe
- Does not alter the appearance of the surface
- Does not yellow despite environmental conditions or ageing
- High penetration capacity
- High coverage
- Prevents formation of moss and mold
- Certified as suitable for use on food contact surfaces
- Prevents efflorescence

COVERAGE

With one litre:

Natural stone 20 m²

Coverage rates are approximate and refer to a single coat of the product

Packaging

1 litre cans in box of 12.
5 litre cans in box of 4.

COMPOSITION

Blend of siloxane compounds dispersed in de-aromatized hydrocarbon solvent.

LABELLING

Symbol

St Andrews Cross

Risk Phrases

Flammable. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Safety Phrases

Keep out of the reach of children.

Keep away from food, drink and animal feeding-stuffs. In case of fire use: earth, sand, chemical powder or foam. If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Contains: de-aromatized mineral turpentine.



TECHNICAL INFORMATION

Appearance: liquid

Colour: colourless

Odour: slight odour of hydrocarbon solvent

Density: 0.777 kg/litre

Flash point: 40°C

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and check.

Fila accepts no liability for improper use of its products.

HOW IT'S USED

No dilution: ready to use

Application:

Apply an even, generous coat onto a perfectly clean and dry surface with brush or roller. On vertical surfaces, the airless spray method is recommended. Apply until no more product can be absorbed. Depending on the absorbency of the substrate, a second coat may be required, after 24 hours. On low-absorbency natural stone (such as slate) apply one coat. For concrete or more porous natural stone two coats are needed. On exterior surfaces where oil-repellence is also required, apply a finishing coat of Filatob after 24 hours.

Maintenance:

diluted solution of FilaCleaner



Caution:

When protecting low porosity natural stone, spot test the product in advance on a small trial surface to check for colour changes