

TERRACOTTA

NATURAL STONE

CONCRETE

WALLS



### WHAT IT'S FOR

- Removes mould from walls and claddings
- Acts against the build-up of organic substances: algae, moss, etc.

### ADVANTAGES

- Easy to use spray applicator
- Ideal viscosity: no dripping
- Acts rapidly: spray and wipe
- Very effective for cleaning mould from grouting

### HOW IT'S USED

*Ready for use: do not dilute*

**Application:**

1. Spray product directly onto the surface to be cleaned.
2. Leave to act for about 15 minutes.
3. Rinse with a damp, clean cloth.
4. To prevent mould from forming again we recommend a further application of NoAlgae after Fila Smuffy.

### Packaging

500 ml bottles with spray trigger in box of 12

#### PRECAUTIONS

- do not blend with acids.
- do not dump container in the environment.
- Do not spray on fabrics, plants, metals. Rinse immediately with water if these are sprayed unintentionally.

#### COMPOSITION

Contains: nonionic surfactant < 5%, chlorine bleachers <5%; 3% active Cl solution.

#### LABELLING

Symbol  
St Andrew's Cross  
Risk Phrases



Contact with acids liberates toxic gas. Irritating to skin. Risk of serious damage to eyes.

#### Safety Phrases

Keep out of the reach of children. Avoid contact with eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing and eye/face protection. If swallowed, seek medical advice immediately and show container or label.  
Contains: sodium hypochlorite.

#### TECHNICAL INFORMATION

Appearance: transparent viscous liquid  
Odour: distinctive, pungent  
Density: 1.060 kg/litre  
pH: 13.5

*The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary spot tests and checks.*

*Fila accepts no liability for improper use of its products.*